

zenithinteriors.com

UMBRA Round Acoustic Light Zenith

Features:

An impressive acoustic lighting luminaire that lights up anything from conferences room to communal dining spaces. As the long, rounded silhouette suspends from the ceiling, it creates an intimate atmosphere and contributes a sheltering feeling of home along with an extra touch of cosy.

Design: IMPACT ACOUSTIC

Environmental:

- Cradle to Cradle Certified™
- Product qualifies for LEED v4 specifications on VOC emissions in LEED EQ credit
- SUPPORTED BY CLIMATE KIC

Warranty: 12 year product & 2 year lighting

Finishes:

































100% PET (min. 60% post-consumer)

ARCHISONIC® is a high-performance sustainable acoustic absorber made from up-cycled plastic bottles.

ARCHISONIC® is manufactured at the highest quality standards, yet slight colour and surface deviations caused by the high degree of recycled fiber are an inevitable part of the product characteristics and do not claim warranty services.

Material varies in colour when shown in monitor or in print.

ARCHISONIC:


					
Shell Pink 102	Jute 920	Soft Coral 516	Ice Blue 304	Winter Sky 410	Spearmint 706
					
Succulent 712	Pacific Ocean 432	Marine Blue 864	Deep Sea 918	Midnight 810	Moss 439
					
Nordic Pine 311	Grove 317	Sunshine 846	Honeycomb 139	Warm Stone 105	Linen 107
					
Terracotta 239	Electric Orange 464	Hot Pink 140	Poster Red 662	Grape 540	Garnet 724
					
Snow White 500	Cloud 103	Milk 404	Smoke 442	Ground 108	Slate 444
					
Charcoal 542	Raven 550				

Sound Absorption:

DIN ISO 11654


24 mm

aw 0.55 (no airgap)
 aw 0.65 (50 mm / 2" air gap)
 aw 0.90 (100 mm / 4" air gap)
 aw 0.95 (200 mm / 8" air gap)
 aw 0.95 (300 mm / 11" air gap)




Key Data:

Voltage:	240 V +/- 10% AC/DC
Power:	27 W (small)
Light flux:	1900 lm (small) 5700lm (large)
Protection class:	IP 40 / protection class 1
Colour reproduction:	CRI > 80
Colour consistency:	< 3 SDMC
Energy efficiency:	A++
Life span:	> 50'000 h (L80 B10)
UGR:	< 16
Beam angle:	20° / 40°
Light control:	DALI
27 W (small)	
81 W (large)	
1900 lm (small)	
5700 lm (large)	
IP 40 / protection class 1	
CRI > 80	
< 3 SDMC	
A++	
> 50'000 h (L80 B10)	
< 16	
20° / 40°	
DALI	




Dimensions




Round 400

Dia 400mm
 OH 270mm
 Thickness: 24mm




Round 600

Dia 600mm
 OH 400mm
 Thickness: 24mm




Round 800

Dia 800mm
 OH 530mm
 Thickness: 24mm



Round 1200

Dia 1200mm
 OH 650mm
 Thickness: 24mm



Round 1600

Dia 1600mm
 OH 850mm
 Thickness: 24mm