Zenith

VERSE 2





Features:

Verse 2 offers a larger focus room, capable of comfortably catering to both the single employee or the couple in need of privacy within the open floor plan. It's a space where you can come together as a group to collaborate while minimising the noise from those outside the room. It is fitted with a gallery rail to hang accessories for ideation by the group.

Certified 3 Green Star for acoustics, the room is equipped with air ventilation, adjustable lighting, and acoustic performance. It balances the environment for the group to focus and be comfortable within the room.

Verse 2 can be fitted with a media panel and shelf suitable for video conferencing, which also pairs well with a SOL-Sit lounge on the opposite wall as a seating option.

Options:

- 3 standard room sizes (WxD) with 2 available heights
- Media panel and shelf
- White board or cork board accessories

Design: ZENITH DESIGN STUDIO

Warranty: 5 years

(Refer to Zenith Warranty Document for more details)

Certifications: GECA

Finishes:

Front Wall Panel:	Laminated Glass 6.76mm
Glazed Door:	Frameless Toughened Glass 10mm
Internal Side Walls:	Fabric or Sonic Board
Internal Back Walls:	Laminated Glass 6.76mm, Fabric or
	Sonic Board
External Side Walls:	Fabric
External Back Walls:	Laminated Glass 6.76mm or Fabric
Ceiling Internal:	Sonic Board
Ceiling External:	Standard White 1630 Melamine
Inner/Outer Floor Track: Black - Satin ZPC_001	
Upholstery in fabric categories A, C, D, E and F	
Refer to Verse Fabric Specification	

Frame:





White 1630 Standard Melamine Black 0080 Melamine

Shelf:

Sonic Board:








Black ZPET_003 Light Grey Silver ZPET_004 ZPET_006

Ash Mil ZPET_007 ZF

Milky White ZPET_009

Dimensions:



 Verse 2.1

 OW
 1980mm


 OD
 1380mm

 H
 2200/2400mm (Frame)

 OH
 2370/2600mm (Including fan box)

 Internal Room Size: 1800 x 1200mm

Side walls made up of: 2x 600mmW panels Front & back walls made up of: 2x 900mmW panels



 Verse 2.2

 OW
 1980mm


 OD
 1680mm

 H
 2200/2400mm (Frame)

 OH
 2370/2600mm (Including fan box)

 Internal Room Size: 1800 x 1500mm

Side walls made up of: 1x 600mmW & 1x 900mmW panels Front & back walls made up of: 2x 900mmW panels



 Verse 2.3

 OW 1980mm

 OD 1980mm

 H 2200/2400mm (Frame)

 OH 2370/2600mm (Including fan box)

 Internal Room Size: 1800 x 1800mm

Side walls made up of: 2x 900mmW panels Front & back walls made up of: 2x 900mmW panels

Accessories:



White Board or Cork Board with Black or Dark Brown Leather Strap DIA: 600 & 900mm




Gallery Rail White board or cork board are easily attached and relocated

Back Panel (Internal) Options:



Option 1 Glass & Fabric or Sonic Board Panel



Option 2 Fabric or Sonic Board Panels



Option 3 Glass Panels

Front Panel Options:



Option I LH: Door Panel LH: Door Hinges RH: Glass Panel



Option 3 LH: Door Panel RH: Door Hinges RH: Glass Panel




Option 2 RH: Door Panel RH: Door Hinges LH: Glass Panel



Option 4 RH: Door Panel LH: Door Hinges LH: Glass Panel

GPO Panel:



Left Hand Side

Panel: 600/900mmW Al: 1175mmH A2: 945mmH B1: 805mmH

- B2: 605mmH
- B3: 165mmH

Power Outlet Options:



Right Hand Side

Mirrored

GPO + HDMI + USB + DATA

2x GPO + HDMI + DATA



2x GPO + USB + DATA*



(B)



3x GPO + DATA*



3x GPO + USB*




3x GPO + HDMI

Note: *not available as a power outlet option when a media panel has been selected.


Media Panel: (Side Walls only)

TV & TV bracket not included




Verse 2.1: Option 1A

Media Panel 2x 600mmW: LH GPO, RH switch & RH shelf Fabric or Sonic Board (Internal) TV Bracket Height: 1175mm (Seated Level) TV Size: 42" - 45"



Verse 2.2. Option 2A

Media Panel RH 600mmW & LH 900mmW: LH GPO, RH switch & RH shelf Fabric or Sonic Board (Internal) TV Bracket Height: 1175mm (Seated Level) TV Size: 42" - 65"



Verse 2.3: Option 3A

Media Panel x2 900mmW: LH GPO, RH switch & RH shelf Fabric or Sonic Board (Internal) TV Bracket Height: 1175mm (Seated Level) TV Size: 42" - 65"




 Verse RH Shelf

 OW
 710mm

 OD
 330 & 180mm


 OH
 50mm

 Installed Height: 720mm




Verse 2.1: Option 1B

Media Panel 2x 600mmW: RH GPO, LH Switch & LH shelf Fabric or Sonic Board (Internal) TV Bracket Height: 1175mm (Seated Level) TV Size: 42" - 45"



Verse 2.2: Option 2B

Media Panel LH 600mmW & RH 900mmW: RH GPO, LH switch & LH shelf Fabric or Sonic Board (Internal) TV Bracket Height: 1175mm (Seated Level) TV Size: 42" - 65"



Verse 2.3: Option 3B

Media Panel x2 900mmW: RH GPO, LH switch & LH shelf Fabric or Sonic Board (Internal) TV Bracket Height: 1175mm (Seated Level) TV Size: 42" - 65"



 Verse LH Shelf

 OW
 710mm

 OD
 330 & 180mm

 OH
 50mm

 Installed Height: 720mm

Acoustics:


Verse has been tested in accordance with ISO 717-1:2004 Acoustics – Rating of sound insulation in buildings and of building elements – Airborne sound insulation.

Independent Acoustic Testing shows that Verse can qualify for 3 Green Star Credits for acoustics and can achieve between 28-36Dw at 40dB Ambiance with a Privacy Rating of 64-74, depending on the wall type and material selected.

Normal voice conversations can be heard as a muffled sound in adjoining rooms but cannot be understood.

Verse acoustic performance is comparable to most general use office rooms.

Panel Layers:



Air Ventilation:

Verse 2 has Induction airflow to give the larger room cleaner and better air exchange, with a maximum rating of 250-166L/s for 2-3 people in the space.



Fire Safety:

The fire safety of all surface materials; timber, upholstery and acoustics materials used in Verse are tested and classified by either national or international standards.

No fire hazardous materials are used in the construction. Timber frames use BAL-19 Victorian Ash with natural fire resistance qualities (Higher rated Blackbutt BAL-29 can be used on request). Upholstered frame MDF substrate meets AS 3837, AS 1859.2 & AS 4266.16. Fabrics used in upholstery meets AS 3837 & ISO 5660-1. Interior and roof Sonic Boards meets EN 13501-1; B-s1,d0. Roof and wall acoustic insulation meets ISO 9705 & AS 5637.1. Laminate boards used in the roof meets AS 1859.2/3, AS 4266.13, AS 1539.3, and AS 3837.

The installation or relocation of Verse is not allowed to adversely impact on the regulatory requirements of a building. The location of Verse has to consider the location of exits and paths of travel to exists so as to not restrict the use or access of them.

Verse roof is adaptable to sprinklers and smoke detectors. Check with your local experts on the specific regulations, however if fire sprinklers are required in the booths a flexible pipe is to be used and at least 100mm of clearance above the ceiling to enable the roof to be lifted to gain access to services in the ceiling.


Lighting:

Verse comes with 19W/m LED Strip Lighting and Driver suited for different room sizes with 1800lm/m Natural White (4000K).

Verse lighting brightness can be controlled by a dimmer, and turned off by PIR sensor when the room is unoccupied.

Door / Light Switch Position:

All lighting components are compliant with Asia Pacific regional standards and certification requirements that include, EN 60598-1&2, AS61347.1&2, RCM, CE, RoHs and CCC.



Panel: 600/900mmW Floor Height: 1050mm Depth from Left/Right Side: 100mm External Swing door left or right side Switch can be placed on left hand or right hand front panel

Seismic Safety:

Verse can be anchored to the floor with bolts to keep the room upright in case of seismic activity. On request only. If Seismic is required, then depending on local Electrical Regulations alternative wiring looms may be required. Contact us for more information.

Zenith