



Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 1 of 8

ZENITH (SHANGHAI) HIGH-TECH CO., LTD

L1, BLDN 2, 1788 HANGTANG RD, JINHUI TOWN, FENGXIAN SHANGHAI 201405 CHINA

Sample Description : Basis

Source of Sample : SENT BY CLIENT.
Sample Receiving Date : MAR. 21, 2025
Testing Period : MAR. 21, 2025 TO MAR. 28, 2025

Test Requested	Result
ANSI/BIFMA X5.1-2017 (R2022): GENERAL-PURPOSE OFFICE CHAIR- AMERICAN NATIONAL STANDARD FOR OFFICE FURNITUR	PASS

Signed for and on behalf of
SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

Arron Lou
Authorized Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.
Hardines

4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgs.com
中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 2 of 8

Test Conducted:

ANSI/BIFMA X5.1-2017 (R2022): General-Purpose Office Chair– American National Standard For Office Furniture

Testing Condition : All the physical test is carry out in indoor ambient.

Nos. of Specimen : 3 pcs.

Type of Chair : Type III

Test Result : Pass

Test Property	Test Method	Test Principle / Requirements	Results
Back Strength Test-Static-Type I & II (Functional Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 5	No loss of serviceability when 667 N (150 lbs.) is applied for 1 min. Applied 70° to the back at 16 in. above the seat.	N/A See note 1
Back Strength Test-Static-Type I & II (Proof Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 5	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 1001 N (225 lbs.) is applied for 1 min. Applied 70° to the back at 16 in. above the seat.	N/A See note 1
Back Strength Test – Static – Type III (Functional Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 6	No loss of serviceability when 667 N (150 lbs.) is applied for 1 min. Applied 90° to the back at 16 in. above the seat.	Pass
Back Strength Test – Static – Type III (Proof Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 6	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 1001 N (250 lbs.) is applied for 1 min. Applied 90° to the back at 16 in. above the seat.	Pass
Drop Test – Dynamic (Functional Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 7	No loss of serviceability when 102kg (225 lbs.) weight free falls from 6 in height to the center of the seat.	Pass
Drop Test – Dynamic (Proof Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 7	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 136kg (300 lbs.) weight free falls from 6 in height to the center of the seat.	Pass
Swivel Test – Cyclic	ANSI/BIFMA X5.1 -2017 (R2022) Clause 8	No loss of serviceability after 60,000 cycles of rotation (360°) under a 122kg (270 lbs.) load on the seat at its max. height. Seat shall then withstand another 60,000 cycles of rotation at its lowest seating position. Total 120,000 cycles.	N/A See note 1
Tilt Mechanism Test – Cyclic – Type I & II	ANSI/BIFMA X5.1 -2017 (R2022) Clause 9	No loss of serviceability after 300,000 cycles under a 109kg (240 lbs.) load to the center of the seat	N/A See note 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC (Shanghai) Technical Service (Group) Co., Ltd.
Hardines

4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgs.com.cn
中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com

Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 3 of 8

Test Property	Test Method	Test Principle / Requirements	Results
Impact test	ANSI/BIFMA X5.1 -2017 (R2022) Clause 10.3	No loss of serviceability in 100,000 cycles impact. A weight of 57kg (125 lbs.) free falls onto the seat from 1.4 in. height.	Pass
Front Corner Load Ease Test – Cyclic – Off Center	ANSI/BIFMA X5.1 -2017 (R2022) Clause 10.4	No loss of serviceability after load each seat front corner with 890N (200 lbs.) for 20,000 cycles, total 40,000 cycles. Note: this test is done after “Impact test” on the same sample.	Pass
Stability Test - Rear Stability for Type III Chairs	ANSI/BIFMA X5.1 -2017 (R2022) Clause 11.3.1	Load the chair with 6 disks, apply a horizontal force to the highest disk, The location of the force application is 6 mm (0.25 in.) from the top of the disk. For chairs with seat height less than 710 mm (28.0 in.), calculate the force as follows: <ul style="list-style-type: none"> • $F = 0.1964 (1195 - H)$ Newton. • $[F = 1.1 (47 - H)$ pounds force.]. H is the seat height in mm. H is the seat height in inches. For chairs with seat height equal to or greater than 710 mm (28.0 in.), a fixed force of 93 N (20.9 lbf.) shall be applied. The chair shall not tip over.	Pass
Stability Test - Rear Stability for Type I and II Chairs	ANSI/BIFMA X5.1 -2017 (R2022) Clause 11.3.2	Load the chair with 13 disks, place the first disk on the seat so it touches the support fixture. The chair shall not tip over.	N/A See note 1
Stability Test – Front Stability	ANSI/BIFMA X5.1 -2017 (R2022) Clause 11.4	The chair is obstructed with a 13mm (½ in.) obstruction to the chair casters/legs. A downward load of 61kg (135 lbs.) is centered 60mm (2.4 in.) from the seat front center edge. The seat shall withstand a 20N (4.5 lbf.) horizontally from the front seat edge without tipping.	Pass
Arm Strength Test Vertical – Static (Functional Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 12	No loss of serviceability when 750N (169 lbs.) is applied for 1 min. The vertical load is uniformly applied along a 127mm (5 in.) length at the apparent weakest point.	N/A See note 1
Arm Strength Test Vertical –Static (Proof Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 12	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 1125N (253 lbs.) is applied for 15 seconds. The vertical load is uniformly applied along a 127mm (5 in.) length at the apparent weakest point.	N/A See note 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC (Shanghai) Technical Service (Shanghai) Co., Ltd. | 4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgs.com.cn
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com

Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 4 of 8

Test Property	Test Method	Test Principle / Requirements	Results
Arm Strength Test Horizontal – Static (Functional Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 13	No loss of serviceability when 445N (100 lbs.) for 1 min. is applied horizontally outward to the armrest at the most forward point of the armrest.	N/A See note 1
Arm Strength Test Horizontal – Static (Proof Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 13	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 667N (150 lbs.) for 15 seconds. is applied horizontally outward to the armrest at the most forward point of the armrest.	N/A See note 1
Back Durability Test – Cyclic – Type I	ANSI/BIFMA X5.1 -2017 (R2022) Clause 14	No loss of serviceability in 120,000 cycles with a 109kg (240 lbs.) in the center of the seat and a 445N (100 lbf.) 90° to the center of the chair back. For chairs with a back width greater than 406mm (16 in.), test at the center of chair back for 80,000 cycles and then 102mm (4 in.) off-center 40,000 cycles, half to each side.	N/A See note 1
Back Durability Test – Cyclic – Type II & III	ANSI/BIFMA X5.1 -2017 (R2022) Clause 15	No loss of serviceability in 120,000 cycles with a 109kg (240 lbs.) in the center of the seat and a 334N (75 lbf.) 90° to the center of the chair back. For chairs with a back width greater than 406mm (16 in.), test at the center of chair back for 80,000 cycles and then 102mm (4 in.) off-center 40,000 cycles, half to each side.	Pass
Caster / Chair Base Durability Test For Pedestal Base Chair	ANSI/BIFMA X5.1 -2017 (R2022) Clause 16.1	No loss of service after 2,000 cycles over a hard surface with 3 obstacles and 98, 000 cycles over a smooth hard surface without obstacles under a 122kg (270 lbs.) load on the seat. Test stroke is 762mm (30 in.) minimum. The caster should not separate under 22N (5 lbs.) pulling force in line with the caster stem after the cycling test.	N/A See note 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Technical Services (Shanghai) Co., Ltd. 4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgs.com.cn
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com

Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 5 of 8

Test Property	Test Method	Test Principle / Requirements	Results
Caster / Chair Base Durability Test For Chairs with Legs	ANSI/BIFMA X5.1 -2017 (R2022) Clause 16.2	No loss of service after 2,000 cycles over a hard surface with 2 obstacles and 98, 000 cycles over a smooth hard surface without obstacles under a 122kg (270 lbs.) load on the seat. Test stroke is 762mm (30 in.) minimum. The caster should not separate under 22N (5 lbs.) pulling force in line with the caster stem after the cycling test.	N/A See note 1
Leg Strength Test – Front Load (Functional Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 17.3	No loss of serviceability when a force of 334N (75 lbf.) is applied to each front leg individually for 1 minute.	Pass
Leg Strength Test – Front Load (Proof Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 17.3	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 503N (113 lbf.) is applied to each front leg individually for 1 minute.	Pass
Leg Strength Test – Side Load (Functional Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 17.4	No loss of serviceability when a force of 334N (75 lbf.) is applied once to each front and rear leg individually for 1 minute.	Pass
Leg Strength Test – Side Load (Proof Load)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 17.4	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 503N (113 lbf.) is applied once to the front and rear leg individually for 1 minute.	Pass
Footrest Static Load Test – Vertical-Functional load (If applicable)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 18.4.1	Apply a force F1 of 445 N (100 lbf.) uniformly along a 102 mm (4 in.) distance along the footrest but not greater than 51 mm (2 in.) from the outside edge at the apparent weakest point of the structure for one (1) minute in the vertical downward direction, maintain force F1 and apply an additional force F2 of 445 N (100 lbf.) to the footrest at the opposing position for an additional one (1) minute. There shall be no loss of serviceability or sudden loss of footrest height.	N/A See note 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgs.com.cn
中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com

Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 6 of 8

Test Property	Test Method	Test Principle / Requirements	Results
Footrest Static Load Test – Vertical-Proof load (If applicable)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 18.4.3	Apply a force of 1334 N (300 lbf.) uniformly along a 102 mm (4 in.) distance along the footrest but not greater than 51 mm (2 in.) from the outside edge at the apparent weakest point of the structure for one (1) minute in the vertical downward direction. The load applied once shall cause no sudden and major change in the structural integrity of the unit. Loss of serviceability is acceptable.	N/A See note 1
Footrest Durability Test – Vertical – Cyclic (If applicable)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 19	No loss of serviceability after 50,000 cycles of a 890N (200 lbf) load vertical along 102mm (4 in.) length of the footrest at the apparent weakest point of the structure.	N/A See note 1
Arm Durability Test – Cyclic	ANSI/BIFMA X5.1 -2017 (R2022) Clause 20	No structural breakage or loss of serviceability when a force of 400N (90 lbf.) is applied to each arm at a 10° angle $\pm 1^\circ$ for 60,000 cycles	N/A See note 1
Out Stop Tests For Chairs With Manually Adjustable Seat Depth (If applicable)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 21	Place 74 kg (163 lb.) rigid mass in the center of the seat, 25 kg (55lbf.) hanging weight shall be held at its most rearward position, then released, permitting it to move forward rapidly and impact the out stops. Repeat for a total of 25 cycles. There shall be no loss of serviceability to the unit.	N/A See note 1
Tablet Arm Static Load Test (If applicable)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 22	Apply a load of 68 kg (150 lb.) through a 203 mm diameter area 25 mm from the edge of the surface at its apparent weakest point, for one (1) minutes. Shall cause no sudden and major change in the structural integrity of the chair at the first load, and after performing the test, the tablet arm must allow egress form the unit; other losses of serviceability are acceptable.	N/A See note 1
Tablet Arm Load Ease Test – Cyclic (If applicable)	ANSI/BIFMA X5.1 -2017 (R2022) Clause 23	A 25kg (55 lb.) bag shall be raised until the entire weight is off the tablet surface and then eased (without impact) onto the surface, repeat for a total of 100,000 cycles without loss of serviceability to the unit.	N/A See note 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgs.com.cn
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com

Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 7 of 8

Test Property	Test Method	Test Principle / Requirements	Results
Structural Durability Test – Cyclic	ANSI/BIFMA X5.1 -2017 (R2022) Clause 24	Place a weight of 109kg (240lbf) in the center of the seat. Apply a force of 334N (75lbf) at an appropriate for 25000cycles by a cycling device. There shall be no loss of serviceability	Pass
Informative - Base Test – Static	ANSI/BIFMA X5.1 -2017 (R2022) Appendix C	No sudden and major change in the structural integrity under 11,120 N (2500 lbs.) compression for 1 min. The weight is then removed and reapplied for 1 min. The center column may not touch the test platform during load applications.	N/A See note 1
Informative – Simultaneous side legs strength test	ANSI/BIFMA X5.1 -2017 (R2022) Appendix H	The chair shall be placed on a test platform with the side legs restrained by a block 11 to 38mm high. All adjustments shall be set at normal use conditions. A force of 334N (75lbs.) per leg shall be applied once to a front and rear leg simultaneous for one minute. Remove force, there shall be no loss of serviceability.	Pass

Note : # 1- N/A means not applicable to this product design.

Remark:

- Since the data and / or information above division line of front page is provided by the applicant, the relevant results or conclusions of this report are only made for these data and / or information, SGS shall not be responsible for the authenticity and integrity of such data and information and the validity of the results and / or conclusions arising therefrom. Testing results only apply to the sample as received.
- The declaration of conformity is based on acceptance limits chosen based on simple acceptance ($w = 0$, $AL = TL$).
Statements of conformity are reported as:
Passed - The measured values were observed in tolerance at the points tested.
Failed - One or more measured values were observed out of tolerance at the points tested.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgs.com
中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com

Test Report

No.: SHHL250301462301FT

Date: MAR. 28, 2025

Page: 8 of 8

Sample Photo:

Received sample (view 1)



Received sample (view 2)



Received sample (view 3)



SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS CSTC (Shanghai) Co., Ltd.
Hardines

4th Building, No.889, Yishan Road, Xuhui District, Shanghai, China 200233 | 3rd Building, Lane 3999, Xiupu Road, Pudong District, Shanghai China 201315 t (86) 400 960 9661 www.sgsgroup.com.cn
中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 | 中国·上海·浦东新区秀浦路3999弄3号楼 邮编: 201315 t (86) 400 960 9661 sgs.china@sgs.com